Altered State Porcelain Stone®

Color Palette






AV341 ▶ White Hot



AV344 ▶ Copper Core



AV345 ► Melting Point



AV343 Acid Wash

Features and Benefits

- Artfully mimicking the beauty of oxidized and aged steel, copper, iron, zinc, and chromium
- 6 x 24, 12 x 24, 24 x 24, and 2 x 12 sheet mounted mosaics add to design versatility
- All sizes are rectified and modular with a minimum of 3mm grout joint
- Available in 5 metal inspired colors
- $\bullet \mbox{Cross-Sheen}^{\mbox{\tiny (B)}}$ finish for easy cleaning
- Altered State contains a minimum of 4% pre-consumer recycled content and is manufactured by Crossville[®] using processes that is Green SquaredSM certified.
- Made in U.S.A.



Floor: **AV341** ▶ White Hot 24 x 24 and **AV342** ▶ Steel Gaze 24 x 24 on floor Walls: Color By Numbers **WT02** ▶ Tea for Two 4 x 12 Gloss



Altered State Porcelain Stone®



Mosaics Available in all colors

2 x. in U 297

2 x 12 Mosaics available in UPS. (Mounted on a 297 mm x 297 mm sheet.)

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



Sizes & Finishes

Sizes & Fillishes				
Field Tile		Available in all colors		
Nominal (in)	Actual (mm)	Thickness (mm)	Finish	
6 x 24	147 x 597	10.5	UPS	
12 x 24	297 x 597	10.5	UPS	
24 x 24	597 x 597	10.5	UPS	

Note: All field tile is rectified and modular with a minimum 3mm grout joint. Actual measurements stated in inches indicate tile is calibrated (non-rectified). Actual measurements stated in mm indicated tile is rectified.

Please Note: Tile is directional. Please install accordingly.

Mosaics		Available in all colors		
Nominal (in)	Actual (mm)	Thickness (mm)	Finish	
2 x 12*	47 x 297	10.5	UPS	

*Mounted on a 297 x 297 sheets with a 3mm grout joint. The 2 x 12 mosaic can be used in linear drain shower pans as long as the 12 inch side runs parallel to the drain.

Coordinating Trim		Available in all colors	
Nominal (in)	Actual (mm)	Thickness (mm)	Finish
6 x 24 Single Bullnose	147 x 597	10.5	UPS



6 x 24 Single Bullnose

Wet Dynamic Coefficient of Friction Range

UPS	0.42 - 0.52	AcuTest sm

Product Performance

FIGURE		
Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Shade & Texture Index

Altered State has a shade variation of V3.



V2 Slight Variation

V3 Moderate Variation

4 Substantial Variation

This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.



Altered State

Crossville, Inc.

PO Box 1168 Crossville, TN 38557 Phone931.484.2110Fax931.456.2956E-MailCrossc@CrossvilleInc.comWebCrossvilleInc.com

Recommended Use

Altered State is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Altered State is not recommended for exterior horizontal surfaces or exterior paving. If offset pattern is required for tiles 18 inches or longer, Crossville[®] recommends an offset of not greater than 33%. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage. See CrossvilleInc.com for detailed installation instructions.

EcoCycle Tile Process™

Altered State contains a minimum of 4 percent pre-consumer recycled content and is manufactured by Crossville[®] using processes that recycle nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back[™] Program. For more information, visit CrossvilleInc.com/ green.

Green SquaredsM Certified

Crossville[®] has earned Green Squared[™] certification from the Tile Council of North America (TCNA) for its entire U.S.-manufactured porcelain product line-up, as well as its manufacturing processes. The company is among the first ever recipients of this certification standard for the tile industry. TCNA developed the Green Squared certification under American National Standards Institute (ANSI) process. The multi-attribute program (ANSI A138.1) scores products in five categories of performance: product characteristics, manufacturing, corporate governance, innovation and end-of-life. Crossville's certified products and processes received stringent evaluation from Scientific Certification Systems (SCS), the green building industry's longest standing third-party certifier.

Trade Organizations

Care and Maintenance

Regular cleaning is the best way to keep Altered State tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More Information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Hydrotect

Our porcelain tiles are available with Hydrotect[™]. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.

WHYDROTECT

by 🔶 CROSSVILLE.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-tozero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

Crossville[®] Sample Express

Sample fulfillment & Help Line Samples@CrossvilleInc.com 1800 221.9093

Loose Samples for


Architects & Designers

Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Replacement Chips for PSS Rack Max. of 5, 2 x 2 chips per color

Standard Shipping UPS Ground









RCELAI



FS-ALTDST-17 REV. 8-2017